

<b>Available Lengths:</b>	27, 40, 48 in (69, 102, 122 cm)
<b>Tube Diameter:</b>	2 in (5.1 cm)
<b>Discharge Size:</b>	1-1/2 in (3.8 cm) or 2 in (5.1 cm)
<b>Discharge Types:</b>	Hose barb or tri-clamp
<b>Hose Size:</b>	1-1/2 in (3.8 cm) or 2 in (5.1 cm)

	<b>Electric Motor</b>	<b>Air Motor</b>
<b>Maximum Flow:</b>	7 gpm (27 lpm)	7 gpm (27 lpm)
<b>Maximum Head:</b>	300 ft (91 m)	300 ft (91 m)
<b>Maximum Specific Gravity:</b>	1.8	1.8
<b>Maximum Viscosity:</b>	100,000 cP	100,000 cP

<b>Tube Material:</b>	316 stainless steel
<b>Shaft Material:</b>	316 stainless steel
<b>Stator Materials:</b>	Buna, FKM, or PTFE
<b>Seal Materials:</b>	Carbon, Ceramic, FKM, EPDM, SiC, Buna, or Kalrez®
<b>O-ring Materials:</b>	Buna, FKM, EPDM, or PTFE encapsulated silicone

<b>Maximum Temperature:</b>	180° F (82° C)
<b>Minimum Temperature:</b>	-20° F (-29° C)

*FDA-compliant option available. Please contact factory for details.*