



POLYSPUN: DEPTH FILTER CARTRIDGES (Meltblown)



100% Pure Polypropylene
Extruded for structural strength without center core.

High-Temperature Performance for Plating solutions and most chemicals up to 140°F (60°C), Water to 212°F (100°C)
(See chemical resistance guide T-102)

Unique Fiber Bonding
Four to five hundred layers of melt-bonded polypropylene fiber.

Selective Depth Filtration
1, 5, 10, 20, 50, or 75 Micron

MODEL	MICRON RATING	NOMINAL LENGTH	CARTON QUANTITY
01U9.8	1	9.75"	30
01U10	1	10"	30
01U20	1	20"	15
01U30	1	30"	15
05U9.8	5	9.75"	30
05U10	5	10"	30
05U20	5	20"	15
05U30	5	30"	15
10U9.8	10	9.75"	30
10U10	10	10"	30
10U20	10	20"	15
10U30	10	30"	15

MODEL	MICRON RATING	NOMINAL LENGTH	CARTON QUANTITY
20U10	20	10"	30
20U20	20	20"	15
20U30	20	30"	15
30U10	30	10"	30
30U20	30	20"	15
30U30	30	30"	15
50U10	50	10"	30
50U20	50	20"	15
50U30	50	30"	15
75U10	75	10"	30
75U20	75	20"	15
75U30	75	30"	15

MICRON	1	5	10	20	30 - 75
PRESSURE DROP (PSI)**	5	2	1	.7	.5

**Aqueous flow at 5 U.S. GPM (19 LPM) per 10" length
* Order in carton quantity



SERFILCO®

Chemical resistant pumps & filters engineered for industry

MEDIA USED PER CHAMBER / SYSTEM

TYPE	FLOW RATE (GPH)	DOE CARTRIDGE	SOE CARTRIDGE	DISC	BAG	CARBON	Ø6" PLEATED CARTRIDGES
'L'	Up to 2,000	✓	✓		✓	✓	
'S'	Up to 4,000	✓	✓	✓	✓	✓	
'G'	Up to 7,500	✓	✓	✓	✓	✓	
'JM'	2,200 to 5,400	✓	✓	✓	✓	✓	✓
'HM'	Up to 3,200		✓				✓
'PLB'	Up to 9,000		✓				✓
'FM'	5,400 to 9,400	✓	✓	✓		✓	✓
MEGA FLO	6,000 to 30,000	✓	✓	✓		✓	✓
GUARDIAN	3,500 to 8,500	✓	✓	✓	✓	✓	✓



'L'



'S'



'G'



'JM'



'HM'



'PLBHE'



'FM'



'MEGA-FLO'



'GUARDIAN'