## SPH Series

Plastic Filter Housings





- Economical alternative to metal filter housings in low pressure and cold water applications
- · Rugged design provides trouble-free service
- · Ideal for corrosive or sensitive fluids
- Holds 10 and 20 inch length cartridges with DOE or internal o-ring end cap configurations
- Holds standard 2 ½" and large 4½" diameter cartridges.
- High temperature housings made of reinforced Nylon for use up to 200°F (93°C)
- Meets FDA requirements for potable water and food and beverage applications.
- Optional mounting bracket available for easy installation

## **Applications**

Water Chemicals
Food & Beverage Electronics

DI Water Inks / Paints / Coatings

Coolants Pulp & Paper

# **Specifications & Operating Parameters**

## **Maximum Operating Pressure**

125 psig (8.75 bar) @ 125°F (93°C)

#### Minimum / Maximum Temperature

40°F (°C) / 125°F (93°C)

#### **Connections**

Inlet /Outlet:

Standard: 1/2" or 3/4" FNPT

Heavy Duty (BB): 1" or 1 1/2" FNPT

#### Materials of Construction

Head: FDA grade Polypropylene Clear Sump: Styrean-Acrylonitritle Opaque Sump: Polypropylene

## Gaskets


Standard EPR Optional Viton

## **Options**

Mounting Bracket Kits (See ordering guide for details)

# **Dimensions**

MODEL	А	В	С	D	E	F
SPH5	4.28" (10.9 cm)	1.57" (4.0 cm)	1.18" (3.0 cm)	0.16" (.40 cm)	7.5" (19.0 cm)	5.7" (14.5 cm)
SPH10	4.72" (12.0 cm)	1.57" (4.0 cm)	1.18" (3.0 cm)	0.16" (.40 cm)	10.5" (26.7 cm)	11.8" (30.0 cm)
SPH20	4.72" (12.0 cm)	1.57" (4.0 cm)	1.18" (3.0 cm)	0.16" (.40 cm)	20.47" (52.0 cm)	22.8" (57.9 cm)
SPH10C	5.35" (13.6 cm)	2.22" (5.6 cm)	2.28" (5.8 cm)	0.23" (0.58 cm)	10.4" (26.5 cm)	12.5" (31.8 cm)
SPH20C	5.35" (13.6 cm)	2.22" (5.6 cm)	2.28" (5.8 cm)	0.23" (0.58 cm)	20.47" (52.0 cm)	22.8" (57.9 cm)
SPH10BB	7.28" (18.5 cm)	3.03" (7.7 cm)	3.03" (7.7 cm)	0.275" (0.70 cm)	11.33" (28.8 cm)	14.0" (35.6 cm)
SPH20BB	7.28" (18.5 cm)	3.03" (7.7 cm)	3.03" (7.7 cm)	0.275" (0.70 cm)	21.25" (54.0 cm)	24.0" (61.0 cm)
SPH10HT	5.35" (13.6 cm)	2.22" (5.6 cm)	2.28" (5.8 cm)	0.23" (0.58 cm)	10.4" (26.5 cm)	12.5" (31.8 cm)
SPH20HT	5.35" (13.6 cm)	2.22" (5.6 cm)	2.28" (5.8 cm)	0.23" (0.58 cm)	20.47" (52.0 cm)	22.8" (57.9 cm)



## Models

MODEL	COLORS (HEAD/ SUMP) FEATURES	CARTRIDGE LENGTH	CONNECTION	GASKET	OPTIONAL MOUNTING KIT
Standard Residential SPHWW-5-12 SPHWC-5-12 SPHKB-10-34 SPHKB-20-34	WW'= White/White WC = White/Clear KB = Black/Blue	5 = 4 7/8" 10 = 9 7/8" 20 = 20"	12 = ½" 34 = ¾"	– E = EPR (Standard) V = Viton	- BK1
Commercial SPHKB-10-34C SPHKB-20-34C SPHKC-10-34C SPHKC-20-34C-PR	KB = Black/Blue KC = Black/Clear PR = Pressure Release Valve	10 = 9 7/8" 20 = 20	12 = ½" 34 = ¾"	E = EPR (Standard) V = Viton	BK2
Big Blue SPHKB-10-1BB SPHKB-20-1BB SPHKC-10-15BB SPHKC-20-15BB	KB = Black/Blue KC = Black/Clear	10 = 9 7/8" 20 = 20"	1 = 1" 15 = 1½"	E = EPR (Standard) V = Viton	BK3
Valve-in-Head SPHWW-10-34VH SPHWC-10-34VH	WW = White/White WC = White/Clear	10*	1 = 1" 15 = 1½"	E = EPR (Standard) V = Viton	Not Available
High Temperature SPHRR-10-34HT SPHRR-10-34HT	RR = Red/Red	10*	34 = ¾"	E = EPR (Standard) V = Viton	BK2

# Filter Housings

Shelco manufactures a full line of filter housings. From our rugged single cartridge housings to our heavy duty multi-cartridge housings and bag filter housings, Shelco is the perfect choice for your filtration solutions.